

# SOILS

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

## 26



OPTION OF CENTRE /  
SIDE SHIFT GEAR LEVER

POWER PACKED  
ENGINE

TWIN PROJECTOR  
HEADLAMPS

AGRI, IND. & TURF  
TYRE OPTION

HEAVY DUTY  
FRONT AXLE



**COST**  
EFFICIENT  
MECHANICAL TRACTORS

MADE OF  
**REAL**  
STEEL

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
« FOR YOUR FIELD »**

**26**

**SOLIS**



FEATURES	<b>26</b>
<b>ENGINE</b>	
Engine Type	3 Cylinder Diesel Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM	2500
Air Cleaner	Dry with Clogging Sensor
Cold Start	Standard
Max. Torque (Nm)	76.3
Exhaust	Silencer in The Engine Compartment, Downward Discharge
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	Heavy Duty Axle
Transmission	Sliding Mesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	16.2@2815 fly up
Minimum Speed (Km/Hr)	1.64@2500 rated
<b>BRAKES</b>	
Brakes	Oil Bath Brake
Type of Actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential lock	Yes, Foot Operated
<b>PTO</b>	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power Steering
<b>ELECTRICAL</b>	
Battery	12 V, 65 Ah
Type of Actuation	12V, 42 A
Parking Brake	Standard
<b>HYDRAULICS</b>	
3 Point Linkage	Cat 1 - N
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	1DA
Lift Rods	Standard
Lifting Capacity (Kg)	600 / 775 (Optional)
Litre Per Minute (LPM)	13.5

FEATURES	<b>26</b>		
<b>SAFETY SWITCH</b>			
PTO Safety	Standard		
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
<b>CAPACITY (LITRE) (+/-5%)</b>			
Fuel Tank (Ltr.)	28		
<b>TURNING RADIUS</b>			
Without Brakes (m)	3.18 (RHS), 3.10 (LHS)		
<b>TYRE (STANDARD)</b>			
Front	6.00-12		
Rear	8.30-20		
<b>DIMENSION &amp; WEIGHT (+/-5%)</b>			
Weight (kg)	1070, 1265 with Cabin		
Wheel Base (mm)	1560		
Total Length (mm)	2760		
Total Width (mm)	1075 (max) - 1055 (min)		
Height (mm) Up to ROPS	1955		
Min. Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	835		
<b>OTHERS</b>			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with Std. Ballast	Front weights - 2 x 15 Kg		
Trailer Hitch	Drawbar / Optional Towbar		
ROPS	Yes		
Cabin Option	Yes		
<b>TYRES</b>			
Radial Agri: Front   Rear 6.5/80-12 280/70 R18	Turf: Front   Rear 23x8.50-12 33x15.5-16.5	Ind: Front   Rear 23x8.50-12 33x15.5-16.5	Galaxy Pro 220/55R12 280/70R16
Front loader	YES optional		

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

**DEALER STAMP**



**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com