

SOILS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26
SHUTTLE XL



INTEGRATED
LOADER
JOYSTICK (OPTIONAL)

HEAVY DUTY
FRONT AXLE

QUICK ATTACHED
LOADER

SYNCHROMESH
SHUTTLE

9 FORWARD
X 9 REVERSED GEAR



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

**THE TOUGHEST
PERFORMER
FOR YOUR FIELD**

**26
SHUTTLEXL**

SOLIS



FEATURES		26 SHUTTLEXL (9+9)
ENGINE		
Engine Type	3-Cylinder Diesel Engine	
HP Category	26	
No. of Cylinders	3	
Aspiration	Naturally	
Cubic Capacity (cc)	1319	
Rated RPM (+/-25mm)	2500	
Air Cleaner	Dry	
Cold Start	Standard	
Max Torque (Nm)	76.3	
Exhaust	Silencer in the Engine Compartment, Downward Discharge	
TRANSMISSION		
Drive	4WD	
Clutch	Single Clutch	
Gearbox	9 Forward + 9 Reverse	
Front Axle	Heavy Duty Axle	
Transmission	Constant Mesh with Synchromesh Shuttle Lever	
SPEED (FORWARD)		
Maximum Speed (Km/Hr)	21.46 @2760 fly up	
Minimum Speed (Km/Hr)	1.14@rated	
BRAKES		
Brakes	Oil Immersed	
Type of Actuation	Mechanical	
Parking Brake	Independent	
DIFFERENTIAL LOCK		
Differential Lock	Yes, Foot Operated	
PTO		
PTO (RPM)	540/540E	
PTO (Actuation)	Mechanical	
STEERING		
Steering	Power Steering	
ELECTRICAL		
Battery	12V, 65 Ah	
Alternator	12V, 42 A	
Seven Pin Trailer Socket	Standard	
HYDRAULICS		
3 Point Linkage	Cat 1-N	
Stay Bars	Anchor Chain	
Additional Hydraulic Circuit	1 DA	
Hydraulic Lifting Capacity (Kg)	600 / 775 (Optional)	
Lift Rods	Standard	
Litre Per Minute (LPM)	17.8	
SAFETY SWITCH		
PTO Safety	Standard	

FEATURES		26 SHUTTLEXL (9+9)	
Neutral Safety Switch	Standard		
Clutch Safety Switch	Standard		
CAPACITY (LTRS)(+/-5%)			
Fuel Tank (Ltr.)	20		
TURNING RADIUS			
Without Brakes (m) as per Standard Tyres	3.02 (RHS), 3.15 (LHS)		
TYRE			
Front	6.00-12		
Rear	8.30-20		
DIMENSION & WEIGHT(+/-5%)			
Weight (Kg)	1250		
Wheel Base (mm)	1570		
Total Length (mm)	2895		
Total Width (mm)	1215 (max)-1050 (min)		
Height (mm) Up to ROPS	2325		
Min Ground Clearance (mm)	240		
Front Track (mm)	885		
Rear Track (mm)	960		
OTHERS			
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard		
Front & Rear Weights with Std. Ballast	Front Weights-2 x 15		
Trailer Hitch	Towbar, Drawbar (Optional)		
ROPS	Yes		
OPTIONAL FEATURES			
Cabin Option	Optional Only Heater		
TYRES			
Radial Agri: Front Rear 6.5/80-12 280/70 R18	Turf: Front Rear 25x8,50-14 13.60-16	Ind: Front Rear 23x8,50-12 33x15,50-16,5	Galaxy Pro R- 280/70R16
Front loader	Yes Optional		

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com